



NeoSeal Rubber Lubricant

MATERIAL SAFETY DATA SHEET (GHS)

Last Revised: Jan-15

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: NeoSeal Rubber Lubricant
PRODUCT USE: For SWR piping systems

MANUFACTURER: NeoSeal Adhesive Pvt. Ltd.
 Plot# 628/7, GIDC Savli, At. Manjusar
 Dis. Vadodara - 391775, Gujarat, India
 Tel. +91-9099 -935744

SECTION 2 - HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Acute Toxicity: None Known	Acute Toxicity: None Known	None Known
Skin Irritation: Category 3	Chronic Toxicity: None Known	
Skin Sensitization: NO		
Eye: Category 2B		

GHS LABEL:



OR



WHMIS CLASSIFICATION:

Not Regulated

Hazard Statements

H317: May cause an allergic skin reaction

Precautionary Statements

P262: Do not get in eyes, on skin, or on clothing
 P233: Keep container tightly closed
 P271: Use only outdoors or in a well-ventilated area

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS:

CAS#	EINECS #	REACH	CONCENTRATION
CAS#	EINECS #	Pre-registration Number	% by Weight

No hazardous ingredients

All of the constituents of this adhesive product are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that listing.

*Indicates this chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372).

indicates that this chemical is found on Proposition 65's List of chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION 4 - FIRST AID MEASURES

Contact with eyes: Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately.
Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. If irritation develops, seek medical advice.
Inhalation: Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen. Seek medical advice.
Ingestion: Rinse mouth with water. Give 1 or 2 glasses of water or milk to dilute. Do not induce vomiting. Seek medical advice immediately.

SECTION 5 - FIREFIGHTING MEASURES

Suitable Extinguishing Media: Carbon dioxide, foam or dry chemical

Unsuitable Extinguishing Media: None known

Exposure Hazards: Irritating organic vapors

Combustion Products: No information available

	HMIS	NFPA	
Health	1	1	1-Slight
Flammability	1	1	2-Moderate
Reactivity	0	0	3-Serious
PPE	B		4-Severe

Protection for Firefighters: Self-contained breathing apparatus or full-face positive pressure airline masks.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions: Prevent contact with skin or eyes (see section 8).
Environmental Precautions: Prevent product or liquids contaminated with product from entering sewers, drains, soil or open water course.
Methods for Cleaning up: Soak up with inert absorbent material. Store in a partly filled, closed container until disposal.

SECTION 7 - HANDLING AND STORAGE

Handling: Avoid avoid contact with eyes, skin and clothing.
 Do not eat, drink or smoke while handling.

Storage: Store below 54°C (130°F) to preserve shelf life. Keep container tightly closed when not in use.
 Follow all precautionary information on container label and product bulletins.

SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:	Component	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA STEL:	OSHA PEL-Ceiling	CAL/OSHA PEL	CAL/OSHA Ceiling	CAL/OSHA STEL
	No Hazardous Ingredients	NE	NE	NE	NE	NE	NE	NE	NE

Engineering Controls: Use local exhaust as needed.
Monitoring: Maintain breathing zone airborne concentrations below exposure limits.

Personal Protective Equipment (PPE):

Eye Protection: Avoid contact with eyes, wear splashproof chemical goggles.
Skin Protection: Prevent contact with the skin as much as possible. Chemical resistant gloves should be used for frequent immersion.
 Use of rubber or plastic gloves should provide adequate protection when normal adhesive application practices and procedures are used for making structural bonds.

Respiratory Protection: None needed for normal use

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Whitesh paste	Evaporation Rate:	N/A
Odor:	None	Flammability:	None Known
pH:	7	Flammability Limits:	LEL: Not Established
Melting/Freezing Point:	Not Applicable		UEL: Not Established
Boiling Point:	Not Applicable	Vapor Pressure:	< 10mm Hg @ 25°C (77°F)
Flash Point:	> 230°C (440°F)	Vapor Density:	N/A
Specific Gravity:	0.950 @25°C (77°F)	VOC Content	0%
Solubility:	Neglibibe		
Auto-ignition Temperature:	Not Applicable		
Decomposition Temperature:	Not Applicable		

SECTION 10 - STABILITY AND REACTIVITY

Stability:	Stable
Hazardous decomposition products:	None (non-thermal)
Conditions to avoid:	None Known
Incompatible Materials:	None Known

SECTION 11 - TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eye and Skin Contact

Acute symptoms and effects:

Inhalation:	None Known
Eye Contact:	May cause eye irritation
Skin Contact:	May cause skin irritation
Ingestion:	None Known

Chronic (long-term) effects: None known to humans

Toxicity:	LD ₅₀	LC ₅₀
No Hazardous Ingredients	Not Available	Not Available

<u>Reproductive Effects</u>	<u>Teratogenicity</u>	<u>Mutagenicity</u>	<u>Embryotoxicity</u>	<u>Sensitization to Product</u>	<u>Synergistic Products</u>
Not Established	Not Established	Not Established	Not Established	Not Established	Not Established

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity:	None Known
Mobility:	Note Established
Degradability:	Note Established
Bioaccumulation:	Note Established

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult disposal expert.

SECTION 14 - TRANSPORT INFORMATION

Proper Shipping Name:	None
Hazard Class:	Not regulated as a hazard
Secondary Risk:	None
Identification Number:	None
Packing Group:	None
Label Required:	None
Marine Pollutant:	NO

TDG INFORMATION

TDG CLASS:	Not Regulated
SHIPPING NAME:	Not Regulated
UN NUMBER/PACKING GROUP:	Not Regulated

SECTION 15 - REGULATORY INFORMATION

Precautionary Label Information:	Irritant	Ingredient Listings:	USA TSCA, Europe EINECS, Canada DSL, Australia AICS, Korea ECL/TCCL, Japan MITI (ENCS)
Symbols:	Xi		
Risk Phrases:	R-36/38 Irritating to eyes and skin.		
Safety Phrases:	S-2/3 Keep in a cool place, out of reach of children. S-7 Keep container tightly closed when not in use. S-24/25 Avoid contact with skin and eyes. S-35 Dispose of material and container in a safe way.	S-29 Do not empty into drains, storm drains or watercourses. S-37/39 Wear suitable gloves and eye protection. S-45 If seeking medical advice show physician label or SDS. S-51 Use only in well ventilated areas	

SECTION 16 - OTHER INFORMATION

Specification Information:		
Department issuing data sheet:	NeoSeal Adhesive, Safety & Health Department	All ingredients are compliant with the requirements of the European Directive on RoHS (Restriction of Hazardous Substances).
e-mail address:	info@neoseal.net	
Training necessary:	Yes, training in practices and procedures contained in product literature.	
Reissue date / reason for reissue:	27/07/13 / Updated GHS Standard Format	
Intended Use of Product:	Rubber Lubricant for SWR Pipe	

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.