

TECHNICAL DATASHEET

Rubber Gasket Lubricant

GENERAL DESCRIPTION:

NeoSeal® Rubber Gasket Lubricant is water based highly viscous, soft paste like product. It is specially designed to lubricate rubber gaskets of pipelines including PVC and Soil pipes. It is ideal for SWR ring-fit, self-fit, sewer, drain piping system for low to non-pressure application. It aids in assembly of push on type joints to ensure correct fit. NeoSeal Rubber Gasket Lubricant doesn't support bacterial growth and it will not swell rubber components.

FEATURES & BENEFITS:

- Soft paste like easy to apply in wet or dry conditions.
- Non-flammable, Non-toxic, Non-corrosive, No petroleum ingredients.
- Will not deteriorate natural or synthetic rubber, plastic gasket or plastic pipe.
- Safe for potable water system.
- Will not impart taste, color or odor to water in pipelines flushed as per AWWA recommended procedure.
- Doesn't promote bacteria growth.
- RoHS Compliant.
- Ultra-low VOC level.
- Water dispersible

SPECIFICATIONS: OLOR: Milky White
SPECIFIC GRAVITY: 0.96 ± 0.05

AVAILABILITY:

This product is available in 100 ml, 250 ml, 500 ml and 1000 ml, 1 Gal & 5 Gal pail

SHELF LIFE:

One year in tightly sealed containers when not in use. Store product below 44°C (111°F). Manufacturing date code is stamped on the bottom of the container.

QUALITY ASSURANCE:

NeoSeal Rubber Lubricant is carefully evaluated to assure that consistent high quality is maintained. Gas chromatography, and additional in depth testing ensures each batch is manufactured according to standards. A batch identification code is stamped on each can and assures traceability of all materials used in the manufacturing process.