

## TECHNICAL DATASHEET

# Rubber Lubricant

### GENERAL DESCRIPTION:

NeoSeal<sup>®</sup>Rubber Lubricant is milky white, highly viscous, soft paste like water based product. It is specially designed to lubricate rubber gaskets of pipelines including PVC and Soil pipes. It is ideal for SWR ring-fit, self-fit, sewer, drain piping system for low to non-pressure application. It aids in assembly of push on type joints to ensure correct fit. NeoSeal Rubber Gasket Lubricant doesn't support bacterial growth and it will not swell rubber components.

### FEATURES & BENEFITS:

- Soft paste like easy to apply in wet or dry conditions
- Non-flammable, Non-toxic, Non-corrosive
- Will not harm rubber gasket or plastic pipe
- Safe for potable water system
- Doesn't promote bacteria growth
- RoHS Compliant

### SPECIFICATIONS:

COLOR:	Milky white
SPECIFIC GRAVITY:	0.820± 0.05
BROOKFIELD VISCOSITY:	Min. 30,000cP @ 73°F ± 2°F (23°C ± 1°C)

### AVAILABILITY:

This product is available in 100 ml, 250 ml, 500 ml and 1000 ml plastic container

### SHELF LIFE:

One year in tightly sealed containers when not in use. Store product below 44°C (111°F). Manufacturing date code is stamped on the bottom of the container.

### QUALITY ASSURANCE:

NeoSeal Rubber Lubricant is carefully evaluated to assure that consistent high quality is maintained. Gas chromatography, and additional in depth testing ensures each batch is manufactured according to standards. A batch identification code is stamped on each can and assures traceability of all materials used in the manufacturing process.