



## TECHNICAL DATASHEET

### SR 607

### Heat Resistance

### SYNTHETIC RUBBER ADHESIVE

#### DESCRIPTION:

NeoSeal® SR 607 is a light yellow colored, fast drying synthetic rubber adhesive. It is a specially design for the high heat (up to 170°C) application. It provides excellent heat resistance, tack and instant bonding for plywood and laminate. It is perfect adhesive for curved, bending and spherical surface for quick bonding without spring back action.

#### AREA OF APPLICATION:

NeoSeal® SR 607 is commonly used for bonding plywood, furniture and footwear industries. Due to heat resistance power it's ideal to use in the kitchen area furniture, dining table top, HVAC ducting system, chiller/hot water piping insulation, acoustic insulation, under deck insulation, thermal storage system, wall paneling for cold/hot storage etc. It is suitable for bonding laminate, leather, vinyl, metal, PVC to itself and others. Instant bonding makes it ideal for vertical application. It doesn't contain benzene or hazards materials.

#### SPECIFICATIONS:

COLOR	Yellowish
TACK RETENTION TIME (OPEN TIME)	Max. 30 minutes
SPECIFIC GRAVITY:	0.87 ± 0.05
BROOKFIELD VISCOSITY	Min.3000 cps @ (28°C ± 1°C)

\*Tack retention time is generally measured after evaporation of solvent once adhesive applied in thin layer on substrate. Depending upon ambient temperature.

#### APPLICATION:

Surfaces to be bonded should be free from oil, grease, dust and dirt. Stir the adhesive properly prior to use. Apply thin layer of adhesive on joining area of both substrates using brush, spatula or appropriate tool. When one of the substrates is more porous, apply adhesive on this surface last. When glass wool or insulation are bonded, apply adhesive only on duct/pipe/concrete substrate only; not on insulation material. Wait for 5 to 7 minutes for solvent evaporation and tack development (when adhesive becomes touch dry). Align joining area properly and start pressing from one end to other to avoid air bubbles and pressed firmly. Allow to dry min. 24 hours for maximum strength.

**PACKING SIZE:** This product is available in 100ml, 200ml, 500ml, 1Ltr., 5 Ltr., 25 Ltr. in metal can

**SHELF LIFE AND STORAGE:** 1 year in tightly sealed containers. Store between 2°C and 40°C.

#### QUALITY ASSURANCE:

NeoSeal® SR 607 is carefully evaluated to assure that consistent high quality is maintained. Infrared spectroscopy, gas chromatography, and additional in-depth testing ensures each batch is manufactured according to standards. A batch identification code is stamped on each can and assures traceability of all materials and processes used in the manufacturing the adhesive.

#### HEALTH & SAFETY PRECASUTIONS:

Wear personal protective equipment (PPE). Avoid contact with the eyes and skin. In case of direct contact, wash immediately with soap and warm water. Avoid breathing vapour or mist. Use proper ventilation or forced air in application area. Refer the SDS for detailed safety instructions.

**NeoSeal Adhesive Pvt. Ltd.**

628/7, GIDC Savli, At. Manjusar, Vadodara – 391775, Gujarat, INDIA.

Email: info@neoseal.net, Ph: +91-90999 73544; www.neoseal.net