



TECHNICAL DATASHEET
C-35 Cleaner
LOW VOC CLEANER

GENERAL DESCRIPTION:

NeoSeal® C-35 Cleaner is a clear, low VOC emission, water-thin, solvent cleaner. It is specifically formulated to remove grease, oil and dirt from the bonding surfaces of PVC, CPVC, ABS and Styrene pipe and fittings. It is approved for CTS plumbing systems.

APPLICATION:

NeoSeal® C-35 Cleaner is an all-purpose cleaner and can be used on all sizes, classes and schedules of PVC, UPVC, CPVC, ABS and Styrene pipe and fittings. It must be used only as a cleaner, in conjunction with the appropriate cement combination.

SPECIFICATIONS:

COLOR:	Clear
SPECIFIC GRAVITY:	0.798 ± 0.040
BROOKFIELD VISCOSITY:	Water Thin
VOC:	Max. 25 g/l.

STANDARDS AND CERTIFICATION LISTINGS:

- Meets SCAQMD Rule 1171.
- Compliant with LEED® (Leadership in Energy and Environmental Design) Green Building requirement. Credit can be claimed for – Indoor Environmental Quality.

AVAILABILITY:

This product is available in 118ml (4 oz.), 237ml (8 oz.), 473ml (16 oz.) and 946ml (32 oz.) metal can.

SHELF LIFE:

3 years in tightly sealed containers. The date code of manufacture is stamped on the bottom of the container. Stability of the product is limited by the evaporation of the solvent when the container is opened. Evaporation of solvent will cause the cement to thicken and reduce its effectiveness. Adding of thinners to change viscosity is not recommended and may significantly change the properties of the cement.

QUALITY ASSURANCE:

NeoSeal® C-35 Cleaner is carefully evaluated to assure that consistent high quality is maintained. Infrared spectroscopy, gas chromatography, and additional in depth testing ensures each batch is manufactured according to standards. A batch identification code is stamped on each can and assures traceability of all materials used in the manufacturing.